



XAPX2.E36322 Temperature-indicating and -Regulating Equipment - Component

If you notice a change to your XAPX2 Listing Card, click [here](#) to learn more.

[Page Bottom](#)

Temperature-indicating and -Regulating Equipment - Component

[See General Information for Temperature-indicating and -Regulating Equipment - Component](#)

VULCAN ELECTRIC CO

E36322

28 ENDFIELD ST
PORTER, ME 04068-3502 USA

Adjustable thermostats for controlling ovens, liquid baths and similar equipment Model(s) 1A1C followed by 2 or 9, which may or may not be followed by A, B, C, D, F, H, J, K, L, M, O, Q, R, S, T or U, which may or may not be followed by a one to three digit number, when suffix T is used, device must be marked "105 degrees C max."

1A2B followed by 2 or 9, which may or may not be followed by A, B, C, D, F, H, J, K, L, M, O, Q, R, S, T or U, which may or may not be followed by a one to three digit number, when suffix T is used, device must be marked "105 degrees C max."

1A2C followed by 2 or 9, which may or may not be followed by A, B, C, D, F, H, J, K, L, M, O, Q, R, S, T or U, which may or may not be followed by a one to three digit number, when suffix T is used, device must be marked "105 degrees C max."

1B1B followed by 2 or 9, which may or may not be followed by A, B, C, D, F, H, J, K, L, M, O, Q, R, S, T or U, which may or may not be followed by a one to three digit number, when suffix T is used, device must be marked "105 degrees C max."

1B1C followed by 2 or 9, which may or may not be followed by A, B, C, D, F, H, J, K, L, M, O, Q, R, S, T or U, which may or may not be followed by a one to three digit number, when suffix T is used, device must be marked "105 degrees C max."

1B2B followed by 2 or 9, which may or may not be followed by A, B, C, D, F, H, J, K, L, M, O, Q, R, S, T or U, which may or may not be followed by a one to three digit number, when suffix T is used, device must be marked "105 degrees C max."

1B2C followed by 2 or 9, which may or may not be followed by A, B, C, D, F, H, J, K, L, M, O, Q, R, S, T or U, which may or may not be followed by a one to three digit number, when suffix T is used, device must be marked "105 degrees C max."

1C1B followed by 2 or 9, which may or may not be followed by A, B, C, D, F, H, J, K, L, M, O, Q, R, S, T or U, which may or may not be followed by a one to three digit number, when suffix T is used, device must be marked "105 degrees C max."

1C1C followed by 2 or 9, which may or may not be followed by A, B, C, D, F, H, J, K, L, M, O, Q, R, S, T or U, which may or may not be followed by a one to three digit number, when suffix T is used, device must be marked "105 degrees C max."

1C2B followed by 2 or 9, which may or may not be followed by A, B, C, D, F, H, J, K, L, M, O, Q, R, S, T or U, which may or may not be followed by a one to three digit number, when suffix T is used, device must be marked "105 degrees C max."

1C2C followed by 2 or 9, which may or may not be followed by A, B, C, D, F, H, J, K, L, M, O, Q, R, S, T or U, which may or may not be followed by a one to three digit number, when suffix T is used, device must be marked "105 degrees C max."

1D1B followed by 2 or 9, which may or may not be followed by A, B, C, D, F, H, J, K, L, M, O, Q, R, S, T or U, which may or may not be followed by a one to three digit number, when suffix T is used, device must be marked "105 degrees C max."

1D1C followed by 2 or 9, which may or may not be followed by A, B, C, D, F, H, J, K, L, M, O, Q, R, S, T or U, which may or may not be followed by a one to three digit number, when suffix T is used, device must be marked "105 degrees C max."

1D2B followed by 2 or 9, which may or may not be followed by A, B, C, D, F, H, J, K, L, M, O, Q, R, S, T or U, which may or may not be followed by a one to three digit number, when suffix T is used, device must be marked "105 degrees C max."

1D2C followed by 2 or 9, which may or may not be followed by A, B, C, D, F, H, J, K, L, M, O, Q, R, S, T or U, which may or may not be followed by a one to three digit number, when suffix T is used, device must be marked "105 degrees C max."

1E1B followed by 2 or 9, which may or may not be followed by A, B, C, D, F, H, J, K, L, M, O, Q, R, S, T or U, which may or may not be followed by a one to three digit number, when suffix T is used, device must be marked "105 degrees C max."

1E1C followed by 2 or 9, which may or may not be followed by A, B, C, D, F, H, J, K, L, M, O, Q, R, S, T or U, which may or may not be followed by a one to three digit number, when suffix T is used, device must be marked "105 degrees C max."

1E2B followed by 2 or 9, which may or may not be followed by A, B, C, D, F, H, J, K, L, M, O, Q, R, S, T or U, which may or may not be followed by a one to three digit number, when suffix T is used, device must be marked "105 degrees C max."

1E2C followed by 2 or 9, which may or may not be followed by A, B, C, D, F, H, J, K, L, M, O, Q, R, S, T or U, which may or may not be followed by a one to three digit number, when suffix T is used, device must be marked "105 degrees C max."

1G1B followed by 2 or 9, which may or may not be followed by A, B, C, D, F, H, J, K, L, M, O, Q, R, S, T or U, which may or may not be followed by a one to three digit number, when suffix T is used, device must be marked "105 degrees C max."

1G1C followed by 2 or 9, which may or may not be followed by A, B, C, D, F, H, J, K, L, M, O, Q, R, S, T or U, which may or may not be followed by a one to three digit number, when suffix T is used, device must be marked "105 degrees C max."

1G2B followed by 2 or 9, which may or may not be followed by A, B, C, D, F, H, J, K, L, M, O, Q, R, S, T or U, which may or may not be followed by a one to three digit number, when suffix T is used, device must be marked "105 degrees C max."

1G2C followed by 2 or 9, which may or may not be followed by A, B, C, D, F, H, J, K, L, M, O, Q, R, S, T or U, which may or may not be followed by a one to three digit number, when suffix T is used, device must be marked "105 degrees C max."

Investigated to UL 873

1A1B followed by 2 or 9, which may or may not be followed by A, B, C, D, F, H, J, K, L, M, O, Q, R, S, T or U, which may or may not be followed by a one to three digit number, when suffix T is used, device must be marked "105 degrees C max."

1, followed by A, B, C, D, E or G, followed by 1 or 2, followed by B or C, followed by 2 or 9, which may or may not be followed by A, B, C, D, F, H, J, K, L, M, O, Q, R, S, T or U, which may or may not be followed by a one to three digit number, when suffix T is used, device must be marked "105 degrees C max."

Marking: Company name or tradename "E36322" and model designation.

Last Updated on 2017-05-07

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".